

PART NUMBR	RATED VOLTAGE VDC	CAPACITANCE MF	DIMENSIONS mm	SERIES	OPERATING TEMPERATURE	PURPOSE
ESMG401ELL1R0MF11D	400 V	10 MF	10X20	SMG	85 C	GP
ESME451ESS2R2MJ16S	400 V	2.2 MF	10X12.5	SME	85 C	GP
ECLA401ELL1ROMHB5D	400 V	1 MF	8X11	CLA	105 C	ESR
ECLA401ELL3R3MH	400 V	3.3 MF	8X11	CLA	105 C	ESR
EGXE401ETD4R7MJ	400 V	4.7 MF	10X20	GXE HIGH REL	105 C	GP 105
ELXQ401VSN151MP35S	400 V	150 MF	22X35	LXQ	105 C	SNAP IN
ESMG401ELL1ROMP11D	400 V	1 MF	6.3X11	SMG	105 C	GP
ESMG401ELL2R2MHB5D	400 V	2.2 MF	8X11	SMG	85 C	GP
ESMG401ELLAR7MJ16S	400 V	4.7 MF	10X16	SMG	85 C	GP
EKMG401ELL1R0MF11D	400 V	1 MF	6.3X11	KMG	105 C	GP 105
EKMR401VSN221MQ30S	400 V	220 MF	25.5X30	KMR	105 C	SNAP IN
EKMR401VSN681MA40S	400 V	680 MF	35X40	KMR	105 C	SNAP IN
EKMX401ELL220MK25S	400 V	22 MF	12.5X25	KMX HIGH REL	105 C	GP 105
EKMX401ETD100MJ200S	400 V	10 MF	10X20	KMX HIGH REL	105 C	GP 105
EKMX401ETD4R7MJ	400 V	4.7 MF	10X16	KMX HIGH REL	105 C	GP 105
EKXG401ELL100MJ20S	400 V	10 MF	10X20	KXG	105 C	GP 105
EKXJ401EC5100MJ16B+0	400 V	10 MF	10X16	KXJ	105 C	GP 105